



Standard Specification for Concentric-Lay-Stranded Aluminum 1350 Conductors¹

This standard is issued under the fixed designation B 231/B 231M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reappraisal. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reappraisal.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope

1.1 This specification covers aluminum 1350-H19 (extra hard), 1350-H16 or -H26 ($\frac{3}{4}$ hard), 1350-H14 or -H24 ($\frac{1}{2}$ hard), and 1350-H142 or -H242 ($\frac{1}{2}$ hard), bare concentric-lay-stranded conductors constructed with a straight round central wire surrounded by one or more layers of helically layed wires. The conductors are for general use for electrical purposes (Explanatory Note 1 and Note 2).

1.2 The values stated in inch-pound or SI units are to be regarded separately as standard. The values in each system are not exact equivalents; therefore, each system shall be used independently of the other. Combining values from the two systems may result in nonconformance with the specification.

1.2.1 For density, resistivity and temperature, the values stated in SI units are to be regarded as standard.

NOTE 1—Prior to 1975, aluminum 1350 was designated as EC aluminum.

NOTE 2—The aluminum and temper designations conform to ANSI Standard H35.1/H35.1M. Aluminum 1350 corresponds to Unified Numbering System A91350 in accordance with Practice E 527.

NOTE 3—Sealed conductors that are intended to prevent longitudinal water propagation and are further covered/insulated are also permitted within the guidelines of this specification.

2. Referenced Documents

2.1 The following documents of the issue in effect on date of material purchase form a part of this specification to the extent referenced herein:

2.2 *ASTM Standards*:²

B 193 Test Method for Resistivity of Electrical Conductor Materials

B 230/B 230M Specification for Aluminum 1350-H19 Wire for Electrical Purposes

B 263 Test Method for Determination of Cross-Sectional Area of Stranded Conductors

B 354 Terminology Relating to Uninsulated Metallic Electrical Conductors

B 609/B 609M Specification for Aluminum 1350 Round Wire, Annealed and Intermediate Tempers, for Electrical Purposes

B 682 Specification for Standard Metric Sizes of Electrical Conductors

E 29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications

E 527 Practice for Numbering Metals and Alloys (UNS)

2.3 *ANSI Documents*:³

ANSI H35.1 American National Standard Alloy and Temper Designation System for Aluminum

ANSI H35.1M American National Standard Alloy and Temper Designation Systems for Aluminum [Metric]

2.4 *NIST Document*:⁴

NBS Handbook 100—Copper Wire Tables

2.5 *Aluminum Association Document*:⁵

Publication 50, Code Words for Overhead Aluminum Electrical Conductors

3. Classification

3.1 For the purpose of this specification, conductors are classified as follows (Explanatory Note 1 and Note 2):

3.1.1 *Class AA*—For bare conductors usually used in overhead lines.

3.1.2 *Class A*—For conductors to be covered with weather-resistant materials, and for bare conductors where greater flexibility than is afforded by Class AA is required. Conductors intended for further fabrication into tree wire or to be insulated

¹ This specification is under the jurisdiction of ASTM Committee B01 on Electrical Conductors and is the direct responsibility of Subcommittee B01.07 on Conductors of Light Metals.

Current edition approved April 1, 2004. Published May 2004. Originally approved in 1948. Last previous edition approved in 1999 as B 231/B 231M – 99.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ Available from American National Standards Institute (ANSI), 25 W. 43rd St., 4th Floor, New York, NY 10036.

⁴ Available from National Technical Information Service (NTIS), U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

⁵ Available from the Aluminum Association, Inc., 900 19th Street, NW, Suite 300, Washington, DC 20006.

and laid helically with or around aluminum or ACSR messengers, shall be regarded as Class A conductors with respect to direction of lay only (see 7.4).

3.1.3 *Class B*—For conductors to be insulated with various materials such as rubber, paper, varnished cloth, and so forth, and for the conductors indicated under Class A where greater flexibility is required.

3.1.4 *Classes C and D*—For conductors where greater flexibility is required than is provided by Class B conductors.

TABLE 1 Construction Requirements and Recommended Reel Sizes and Shipping Lengths of Aluminum Conductors, Concentric-Lay-Stranded, Class AA, and Class A

NOTE 1—Metric values listed represent a soft conversion and as such they may not be the same as those masses which are calculated from the basic metric density.

| Conductor Size | | | | Required Construction | | Mass | | Rated Strength | | Recommended Package Sizes ^A | | | |
|---------------------------------|-----------------|----------------------------|-------|-----------------------|------------------|------|-----------------------|----------------|------|--|----------------------------------|---|--|
| cmils ^B or AWG | mm ² | Code Words ^C | Class | Number of Wires | Diameter of Wire | | Per 1000 ft, lb | Per km, kg | kips | kN | Reel Designation ^D | Nominal Length of Each Piece, ft ^B | Nominal Mass of Each Length, lb ^B |
| | | | | | in. | mm | | | | | | | |
| 3 500 000 | 1773 | Bluebonnet | A | 127 | 0.1660 | 4.22 | 3345 | 4977 | 58.7 | 261 | RMT 90.45 | 2840 | 9530 |
| 3 000 000 | 1520 | Trillium | A | 127 | 0.1537 | 3.90 | 2840 | 4226 | 50.3 | 223 | RMT 90.45 | 3350 | 9530 |
| 2 750 000 | 1393 | Bitterroot | A | 91 | 0.1738 | 4.42 | 2602 | 3872 | 46.1 | 205 | RMT 90.45 | 3490 | 9100 |
| 2 500 000 | 1267 | Lupine | A | 91 | 0.1657 | 4.21 | 2365 | 3519 | 41.9 | 186 | RMT 90.45 | 3840 | 9100 |
| 2 250 000 | 1140 | Sagebrush | A | 91 | 0.1572 | 3.99 | 2128 | 3166 | 37.7 | 167 | RMT 90.45 | 4270 | 9100 |
| 2 000 000 | 1013 | Cowslip | A | 91 | 0.1482 | 3.77 | 1873 | 2787 | 34.2 | 153 | RMT 90.45 | 4850 | 9100 |
| 1 750 000 | 886.7 | Jessamine | AA | 61 | 0.1694 | 4.30 | 1641 | 2442 | 29.7 | 132 | RMT 90.45 | 5940 | 9760 |
| 1 590 000 | 805.7 | Coreopsis | AA | 61 | 0.1614 | 4.10 | 1489 | 2216 | 27.0 | 120 | RMT 90.45 | 6540 | 9760 |
| 1 510 500 | 765.4 | Gladiolus | AA, A | 61 | 0.1574 | 4.00 | 1417 | 2108 | 25.6 | 114 | RM 68.38 | 3270 | 4880 |
| | | | | | | | | | | | RMT 90.45 | 6880 | 9760 |
| 1 431 000 | 725.1 | Carnation | AA, A | 61 | 0.1532 | 3.89 | 1342 | 1997 | 24.3 | 108 | RM 68.38 | 3440 | 4880 |
| | | | | | | | | | | | RMT 90.45 | 7270 | 9760 |
| 1 351 000 | 694.8 | Columbine | AA, A | 61 | 0.1488 | 3.78 | 1266 | 1884 | 23.4 | 104 | RM 68.38 | 3635 | 4880 |
| | | | | | | | | | | | RMT 90.45 | 7690 | 9760 |
| 1 272 000 | 644.5 | Narcissus | AA, A | 61 | 0.1444 | 3.67 | 1192 | 1774 | 22.0 | 98.1 | RM 68.38 | 3845 | 4880 |
| | | | | | | | | | | | RMT 90.45 | 8170 | 9760 |
| 1 192 500 | 604.2 | Hawthorn | AA, A | 61 | 0.1398 | 3.55 | 1117 | 1662 | 21.1 | 93.5 | RM 68.38 | 4085 | 4880 |
| | | | | | | | | | | | RMT 90.45 | 9340 | 9760 |
| 1 113 000 | 564.0 | Marigold | AA, A | 61 | 0.1351 | 3.43 | 1044 | 1553 | 19.7 | 87.3 | RM 68.38 | 4360 | 4880 |
| | | | | | | | | | | | RMT 90.45 | 9340 | 9760 |
| 1 033 500 | 523.7 | Bluebell | AA | 37 | 0.1671 | 4.25 | 968.4 | 1441 | 17.7 | 78.8 | RM 68.38 | 4670 | 4880 |
| | | | | | | | | | | | RMT 84.45 | 7630 | 7400 |
| 1 033 500 | 523.7 | Larkspur | A | 61 | 0.1302 | 3.31 | 969.2 | 1442 | 18.3 | 81.3 | RM 66.32 | 3815 | 3700 |
| | | | | | | | | | | | NR 48.28 | 1910 | 1850 |
| 1 000 000 | 506.7 | Hawkweed | AA | 37 | 0.1644 | 4.18 | 937.3 | 1395 | 17.2 | 76.2 | RMT 90.45 | 10 060 | 9760 |
| | | | | | | | | | | | RM 68.38 | 5030 | 4880 |
| 1 000 000 | 506.7 | Camellia | A | 61 | 0.1280 | 3.25 | 936.8 | 1394 | 17.7 | 78.3 | RMT 84.45 | 7880 | 7400 |
| | | | | | | | | | | | RM 66.32 | 3940 | 3700 |
| 954 000 | 483.4 | Magnolia | AA | 37 | 0.1606 | 4.08 | 894.5 | 1331 | 16.4 | 72.6 | NR 48.28 | 1970 | 1850 |
| | | | | | | | | | | | RMT 90.45 | 10 400 | 9760 |
| 954 000 | 483.4 | Goldenrod | A | 61 | 0.1251 | 3.18 | 894.8 | 1331 | 16.9 | 75.0 | RM 68.38 | 5200 | 4880 |
| | | | | | | | | | | | RMT 84.45 | 8260 | 7400 |
| 900 000 | 456.0 | Cockscomb | AA | 37 | 0.1560 | 3.96 | 844.0 | 1256 | 16.4 | 68.4 | RM 66.32 | 4130 | 3700 |
| | | | | | | | | | | | NR 48.28 | 2065 | 1850 |
| 900 000 | 456.0 | Snapdragon | A | 61 | 0.1215 | 3.09 | 844.0 | 1256 | 15.9 | 70.8 | RMT 90.45 | 10 900 | 9760 |
| | | | | | | | | | | | RM 68.38 | 5450 | 4880 |
| 795 00 | 402.8 | Arbutus | AA | 37 | 0.1466 | 3.72 | 745.3 | 1109 | 13.9 | 61.8 | RMT 84.45 | 8760 | 7400 |
| | | | | | | | | | | | RM 66.32 | 4390 | 3700 |
| 795 000 | 402.8 | Lilac | A | 61 | 0.1142 | 2.90 | 745.7 | 1110 | 14.3 | 63.8 | NR 48.28 | 2190 | 1850 |
| | | | | | | | | | | | RMT 90.45 | 11 550 | 9760 |
| 750 000 | 380.0 | Petunia | AA | 37 | 0.1424 | 3.62 | 703.2 | 1046 | 13.1 | 58.6 | RM 68.38 | 5775 | 4880 |
| | | | | | | | | | | | RMT 84.45 | 9920 | 7400 |
| 750 000 | 380.0 | Cattail | A | 61 | 0.1109 | 2.82 | 703.2 | 1046 | 13.5 | 60.3 | RM 66.32 | 4960 | 3700 |
| | | | | | | | | | | | NR 48.28 | 2480 | 1850 |
| 715 500 | 362.6 | Violet | AA | 37 | 0.1391 | 3.53 | 671 | 998.5 | 12.8 | 56.7 | RMT 90.45 | 13 080 | 9760 |
| | | | | | | | | | | | RM 68.38 | 6540 | 4880 |
| | | | | | | | | | | | RTM 84.45 | 6930 | 4880 |
| | | | | | | | | | | | RM 66.32 | 5510 | 3700 |
| | | | | | | | | | | | NR 48.28 | 2755 | 1850 |

TABLE 1 *Continued*

| Conductor Size | | Required Construction | | | | Mass | | Rated Strength | | Recommended Package Sizes ^A | | | |
|---------------------------------|-----------------|----------------------------|-------|-----------------------|------------------|------|-----------------------|----------------|------|--|-----------------------------------|---|--|
| cmils ^B or AWG | mm ² | Code Words ^C | Class | Number of Wires | Diameter of Wire | | Per 1000 ft, lb | Per km, kg | kips | kN | Reel Designation ^D | Nominal Length of Each Piece, ft ^E | Nominal Mass of Each Length, lb ^F |
| | | | | | in. | mm | | | | | | | |
| 715 500 | 362.6 | Nasturtium | A | 61 | 0.1083 | 2.75 | 671 | 998.5 | 13.1 | 58.4 | RMT 90.45 RM 68.38 | 14 530 7265 | 9760 4880 |
| 700 000 | 354.7 | Verbena | AA | 37 | 0.1375 | 3.49 | 655.7 | 975.7 | 12.5 | 55.4 | RMT 84.45 RM 66.32 NR 48.28 | 11 260 5630 2815 | 7400 3700 1850 |
| 700 000 | 354.7 | Flag | A | 61 | 0.1071 | 2.72 | 655.8 | 975.8 | 12.9 | 57.1 | RMT 90.45 RM 68.38 | 14 850 7425 | 9760 4880 |
| 650 000 | 329.4 | Heuchera | AA | 37 | 0.1326 | 3.37 | 609.8 | 907.4 | 11.6 | 51.7 | RMT 84.45 RM 66.32 NR 48.28 | 12 130 6065 3035 | 7400 3700 1850 |
| 636 000 | 322.3 | Orchid | AA, A | 37 | 0.1311 | 3.33 | 596.0 | 886.9 | 11.4 | 50.4 | RMT 84.45 RM 66.32 NR 48.28 | 12 400 6200 3100 | 7400 3700 1850 |
| 600 000 | 304.0 | Meadowsweet | AA, A | 37 | 0.1273 | 3.23 | 562.0 | 836.3 | 10.7 | 47.5 | RMT 84.45 RM 66.32 NR 48.28 | 13 140 6570 3285 | 7400 3700 1850 |
| 556 500 | 282.0 | Dahlia | AA | 19 | 0.1711 | 4.35 | 521.4 | 775.8 | 9.75 | 43.3 | RM 66.32 NR 48.28 NR 42.28 | 7270 3635 2425 | 3800 1900 1265 |
| 556 500 | 282.0 | Mistletoe | A | 37 | 0.1226 | 3.12 | 521.3 | 775.7 | 9.94 | 44.3 | RMT 84.45 RM 66.32 NR 48.28 | 14 170 7085 3545 | 7400 3700 1850 |
| 500 000 | 253.3 | Zinnia | AA | 19 | 0.1622 | 4.12 | 468.5 | 697.1 | 8.76 | 38.9 | RM 66.32 NR 48.28 NR 42.28 | 8100 4050 2700 | 3800 1900 1265 |
| 500 000 | 253.3 | Hyacinth | A | 37 | 0.1162 | 2.95 | 468.3 | 696.8 | 9.11 | 40.5 | RMT 84.45 RM 66.32 NR 48.28 | 15 760 7880 3940 | 7400 3700 1850 |
| 477 000 | 241.7 | Cosmos | AA | 19 | 0.1584 | 4.02 | 446.8 | 664.8 | 8.36 | 37.0 | RM 66.32 NR 48.28 NR 42.28 | 8490 4245 2830 | 3800 1900 1265 |
| 477 000 | 241.7 | Syringa | A | 37 | 0.1135 | 2.88 | 446.8 | 664.8 | 8.69 | 38.6 | RMT 84.45 RM 66.32 NR 48.28 | 16 530 8265 4135 | 7400 3700 1850 |
| 450 000 | 228.0 | Goldentuft | AA | 19 | 0.1539 | 3.91 | 421.8 | 627.6 | 7.89 | 35.0 | RM 66.32 NR 48.28 NR 42.28 | 9000 4500 3000 | 3800 1900 1265 |
| 397 500 | 201.4 | Canna | AA, A | 19 | 0.1447 | 3.67 | 372.9 | 554.9 | 7.11 | 31.6 | RM 66.32 NR 48.28 NR 42.28 | 10 180 5090 3395 | 3800 1900 1265 |
| 350 000 | 177.3 | Daffodil | A | 19 | 0.1357 | 3.45 | 327.9 | 487.9 | 6.39 | 28.4 | RM 66.32 NR 48.28 NR 42.28 | 11 560 5780 3855 | 3800 1900 1265 |
| 336 400 | 170.5 | Tulip | A | 19 | 0.1331 | 3.38 | 315.5 | 469.5 | 6.15 | 27.3 | RM 66.32 NR 48.28 NR 42.28 | 12 030 6015 4010 | 3800 1900 1265 |
| 300 000 | 152.0 | Peony | A | 19 | 0.1257 | 3.19 | 281.4 | 418.3 | 5.48 | 24.3 | RM 66.32 NR 48.28 NR 42.28 | 13 490 6745 4495 | 3800 1900 1265 |
| 266 800 | 135.2 | Daisy | AA | 7 | 0.1953 | 4.96 | 250.2 | 372.3 | 4.83 | 21.4 | NR 42.28 NR 36.22 | 5590 2795 | 1400 700 |
| 266 800 | 135.2 | Laurel | A | 19 | 0.1185 | 3.01 | 250.1 | 372.2 | 4.97 | 22.1 | RM 66.32 NR 48.28 NR 42.28 | 15 170 7585 5055 | 3800 1900 1265 |
| 250 000 | 126.7 | Sneezewort | AA | 7 | 0.1890 | 4.80 | 234.4 | 348.8 | 4.52 | 20.1 | NR 42.28 NR 36.22 | 5970 2985 | 1400 700 |
| 250 000 | 126.7 | Valerian | A | 19 | 0.1147 | 2.91 | 234.3 | 348.6 | 4.66 | 20.7 | RM 66.32 NR 48.28 NR 42.28 | 16 190 8095 5395 | 3800 1900 1265 |
| 4/0 | 107.2 | Oxlip | AA, A | 7 | 0.1739 | 4.42 | 198.4 | 295.2 | 3.83 | 17.0 | NR 42.28 NR 36.22 | 7050 3525 | 1400 700 |
| 3/0 | 85.0 | Phlox | AA, A | 7 | 0.1548 | 3.93 | 157.2 | 233.9 | 3.04 | 13.5 | NR 42.28 NR 36.22 | 8890 4445 | 1400 700 |
| 2/0 | 67.4 | Aster | AA, A | 7 | 0.1379 | 3.50 | 124.8 | 185.7 | 2.51 | 11.1 | NR 42.28 NR 36.22 | 11 210 5605 | 1400 700 |

TABLE 1 *Continued*

| Conductor Size | | | | Required Construction | | Mass | | Rated Strength | | Recommended Package Sizes ^A | | | | |
|---------------------------------|-----------------|----------------------------|-------|-----------------------|------------------|------|-----------------------|----------------|-------|--|----------------------------------|---|--|--|
| cmils ^B or AWG | mm ² | Code Words ^C | Class | Number of Wires | Diameter of Wire | | Per 1000 ft, lb | Per km, kg | kips | kN | Reel Designation ^D | Nominal Length of Each Piece, ft ^B | Nominal Mass of Each Length, lb ^B | |
| | | | | | in. | mm | | | | | | | | |
| 1/0 | 53.5 | Poppy | AA, A | 7 | 0.1228 | 3.12 | 98.9 | 147.2 | 1.99 | 8.84 | NR 42.28 | 14 130 | 1400 | |
| 1 | 42.4 | Pansy | AA, A | 7 | 0.1093 | 2.78 | 78.4 | 116.6 | 1.64 | 7.30 | NR 36.22 | 7065 | 700 | |
| 2 | 33.6 | Iris | AA, A | 7 | 0.0974 | 2.47 | 62.2 | 92.6 | 1.35 | 5.99 | NR 36.22 | 8915 | 700 | |
| 4 | 21.1 | Rose | A | 7 | 0.0772 | 1.96 | 39.1 | 58.2 | 0.881 | 3.91 | NR 42.28 | 22 470 | 1400 | |
| 6 | 13.3 | Peachbell | A | 7 | 0.0612 | 1.56 | 24.6 | 36.6 | 0.563 | 2.53 | NR 36.22 | 11 235 | 700 | |
| | | | | | | | | | | | NR 42.28 | 35 710 | 1400 | |
| | | | | | | | | | | | NR 36.22 | 17 855 | 700 | |
| | | | | | | | | | | | NR 42.28 | 56 910 | 1400 | |
| | | | | | | | | | | | NR 36.22 | 28 455 | 700 | |

^A For information only.

^B Conversion factors: 1 cmil = 5.067 E-04 mm², 1 mil + 2.54 E-02 mm, 1 lb/1000 ft = 1.488 E+00 kg/km, 1 ft = 3.048 E-01 m, 1 lb = 4.536 E-01 kg, 1 lbf = 4.448 E-03 kN.

^C Code words shown in this column are from, "Publication 50, Code Words for Overhead Aluminum Electrical Conductors," by the Aluminum Association. They are provided here for information only.

^D See Table 9 for dimensions of standard reels.

4. Ordering Information

4.1 Orders for material under this specification shall include the following information:

4.1.1 Quantity,

4.1.2 Conductor size: square millimetres, if cross-sectional area is specified as a requirement (Section 8 and Tables 1-4),

4.1.2.1 Conductor size, number, and diameter of wires for Class B, C, or D conductors, if cross-sectional area is not specified as a requirement (see 8.2),

4.1.3 Class (see 3.1),

4.1.4 Temper (see 5.1),

4.1.5 Details of special-purpose lays, when required (see 7.2 through 7.5),

4.1.6 Special tension tests if required (see 14.1 and 15.1),

4.1.7 Package size and type (see 17.1 and Table 1 or Table 2),

4.1.8 Special package marking, if required (Section 19),

4.1.9 Heavy wood lagging, if required (see 18.2),

4.1.10 Place of inspection (Section 17), and

4.1.11 Method of cross-sectional area determination if not optional (see 12.1).

5. Requirements for Wires

5.1 Aluminum wire employed in Classes AA and A conductors shall be 1350-H19, unless otherwise specified. The purchaser shall designate the temper of conductors of Classes B, C, and D.

5.1.1 For conductor tempers other than 1350-H19, when temper designations are not more specific in the inquiry and purchase order, the manufacturer shall have the following options on manufacturing method:

5.1.1.1 Strand the conductor from wires drawn to final temper;

5.1.1.2 Strand the conductor from wires drawn to H19 temper and annealed to final temper prior to stranding;

5.1.1.3 Strand the conductor from 1350-H19 wires and anneal the stranded conductor to final temper.

5.2 Before stranding, the aluminum wire used shall meet the requirements of Specifications B 230/B 230M or B 609/B 609M, whichever is applicable.

5.3 All wires in the conductor shall be of the same temper.

6. Joints

6.1 Only cold-pressure joints or electric-butt, cold-upset joints may be made in the six outer finished wires of (1) Class AA conductors composed of seven wires or (2) Class A conductors composed of seven wires used in overhead lines. In other conductors, electric-butt welds, cold-pressure welds, or electric-butt, cold-upset welds may be made in the finished wires composing conductors, but such welds shall not be closer than prescribed in Table 5 (Explanatory Note 3).

7. Lay

7.1 For Class AA conductors composed of seven wires or more, the preferred lay of a layer of wires is 13.5 times the outside diameter of that layer, but the lay shall be not less than 10 nor more than 16 times this diameter.

7.2 For all other classes the lay of a layer of wires shall be not less than 8 nor more than 16 times the outside diameter of that layer, except that for conductors composed of 37 wires or more, this requirement shall apply only to the two outer layers. The lay of the layers other than the two outer layers shall be at the option of the manufacturer, unless otherwise agreed upon.

7.2.1 For conductors to be used in covered or insulated wires or cables, the lay length of the wires shall not be less than 8 nor more than 16 times the outer diameter of the finished conductor. For conductors of 37 wires or more, this requirement shall apply to the wires in the outer two layers. The lay of the layers other than the outer two layers shall be at the option of the manufacturer, unless otherwise agreed upon.

7.3 Other lays for special purposes shall be furnished by special agreement between the manufacturer and the purchaser (Explanatory Note 4).

7.4 The direction of lay of the outer layer shall be right-hand for Classes AA and A and left-hand for other classes, unless the direction of lay is specified otherwise by the purchaser.

TABLE 2 Construction Requirements and Recommended Reel Sizes and Shipping Lengths of Aluminum Conductors, Concentric Lay-Stranded, Classes AA and A

NOTE 1—Sizes selected from Specification B 682.

| Conductor Size, mm ² | Class | Stranding | | | Rated Strength 1350-H19, kN | Recommended Package Sizes ^A | | |
|---------------------------------|-------|-----------------|--------------|-------------|-----------------------------------|--|---------------------------------|---------------------------------|
| | | Number of Wires | Diameter, mm | Mass, kg/km | | Reel Designation ^B | Nominal Length of Each Piece, m | Nominal Mass of Each Length, kg |
| 2000 | A | 127 | 4.48 | 5632 | 294 | RMT 90.45 | 770 | 4325 |
| 1600 | A | 127 | 4.01 | 4512 | 236 | RMT 90.45 | 960 | 4325 |
| 1250 | A | 91 | 4.18 | 3479 | 183 | RMT 90.45 | 1185 | 4130 |
| 1120 | A | 91 | 3.96 | 3123 | 165 | RMT 90.45 | 1320 | 4130 |
| 1000 | A | 91 | 3.74 | 2785 | 151 | RMT 90.45 | 1495 | 4130 |
| 900 | AA | 61 | 4.33 | 2478 | 133 | RMT 90.45 | 1785 | 4425 |
| 800 | AA, A | 61 | 4.09 | 2211 | 119 | RMT 90.45 | 2000 | 4425 |
| | | | | | | RM 68.38 | 1000 | 2215 |
| 710 | AA, A | 61 | 3.85 | 1959 | 105 | RMT 90.45 | 2260 | 4425 |
| | | | | | | RM 68.38 | 1130 | 2215 |
| 630 | AA, A | 61 | 3.63 | 1742 | 96.6 | RMT 90.45 | 2540 | 4425 |
| | | | | | | RM 68.38 | 1270 | 2215 |
| 560 | AA, A | 61 | 3.42 | 1546 | 85.7 | RMT 90.45 | 2860 | 4425 |
| | | | | | | RM 68.38 | 1430 | 2215 |
| 500 | AA | 37 | 4.15 | 1381 | 75.1 | RMT 84.45 | 2430 | 3355 |
| | | | | | | RM 66.32 | 1215 | 1680 |
| | | | | | | NR 48.28 | 610 | 840 |
| 500 | A | 61 | 3.23 | 1379 | 76.5 | RMT 90.45 | 3210 | 4425 |
| | | | | | | RM 68.38 | 1605 | 2215 |
| 450 | AA | 37 | 3.94 | 1245 | 67.7 | RMT 84.45 | 2695 | 3355 |
| | | | | | | RM 66.32 | 1350 | 1680 |
| | | | | | | NR 48.28 | 675 | 840 |
| 450 | A | 61 | 3.06 | 1238 | 68.6 | RMT 90.45 | 3575 | 4425 |
| | | | | | | RM 68.38 | 1790 | 2215 |
| 400 | AA | 37 | 3.71 | 1104 | 61.9 | RMT 84.45 | 3040 | 3355 |
| | | | | | | RM 66.32 | 1520 | 1680 |
| | | | | | | NR 48.28 | 760 | 840 |
| 400 | A | 61 | 2.89 | 1104 | 63.0 | RMT 90.45 | 4010 | 4425 |
| | | | | | | RM 68.38 | 2005 | 2215 |
| 355 | AA | 37 | 3.50 | 982 | 55.1 | RMT 84.45 | 3415 | 3355 |
| | | | | | | RM 66.32 | 1710 | 1680 |
| | | | | | | NR 48.28 | 855 | 840 |
| 355 | A | 61 | 2.72 | 978 | 57.4 | RMT 90.45 | 4525 | 4425 |
| | | | | | | RM 68.38 | 2265 | 2215 |
| 315 | AA, A | 37 | 3.29 | 868 | 48.7 | RMT 84.45 | 3865 | 3355 |
| | | | | | | RM 66.32 | 1935 | 1680 |
| | | | | | | NR 48.28 | 970 | 840 |
| 280 | AA | 19 | 4.33 | 772 | 42.9 | RM 66.32 | 2235 | 1725 |
| | | | | | | NR 48.28 | 1115 | 860 |
| | | | | | | NR 42.28 | 745 | 575 |
| 280 | A | 37 | 3.10 | 771 | 43.2 | RMT 84.45 | 4350 | 3355 |
| | | | | | | RM 66.32 | 2180 | 1680 |
| | | | | | | NR 48.28 | 1090 | 840 |
| 250 | AA | 19 | 4.09 | 689 | 38.3 | RM 66.32 | 2505 | 1725 |
| | | | | | | NR 48.28 | 1250 | 860 |
| | | | | | | NR 42.28 | 835 | 575 |
| 250 | A | 37 | 2.93 | 688 | 39.7 | RMT 84.45 | 875 | 3355 |
| | | | | | | RM 66.32 | 2440 | 1680 |
| | | | | | | NR 48.28 | 1220 | 840 |
| 224 | AA | 19 | 3.87 | 617 | 34.3 | RM 66.32 | 2795 | 1725 |
| | | | | | | NR 48.28 | 1395 | 860 |
| | | | | | | NR 42.28 | 930 | 575 |
| 200 | AA, A | 19 | 3.66 | 552 | 31.6 | RM 66.32 | 3125 | 1725 |
| | | | | | | NR 48.28 | 1560 | 860 |
| | | | | | | NR 42.28 | 1040 | 575 |
| 180 | A | 19 | 3.47 | 496 | 28.4 | RM 66.32 | 3480 | 1725 |
| | | | | | | NR 48.28 | 1730 | 860 |
| | | | | | | NR 42.28 | 1160 | 575 |
| 160 | A | 19 | 3.27 | 440 | 25.2 | RM 66.32 | 3920 | 1725 |
| | | | | | | NR 48.28 | 1955 | 860 |
| | | | | | | NR 42.28 | 1305 | 575 |
| 140 | AA | 7 | 5.05 | 387.0 | 22.2 | NR 42.28 | 1640 | 635 |
| | | | | | | NR 36.22 | 830 | 320 |
| 140 | A | 19 | 3.06 | 386 | 22.1 | RM 66.32 | 4470 | 1725 |
| | | | | | | NR 48.28 | 2230 | 860 |
| | | | | | | NR 42.28 | 1490 | 575 |
| 125 | AA | 7 | 4.77 | 345 | 19.8 | NR 42.28 | 1840 | 635 |
| | | | | | | NR 36.22 | 930 | 320 |

TABLE 3 Construction Requirements of Aluminum Conductors, Concentric-Lay-Stranded, Class B, C, and D

| Conductor Size | | Hard-Drawn Copper Equivalent | | Stranding | | | | | | | | | Direct Current Resistance at 20°C | |
|------------------------|------|------------------------------|------|-----------------|-------------------------------------|-----------------|-------------------------------------|-----------------|-------------------------------------|-------|---|---|-----------------------------------|------|
| cmils ^A | AWG | cmils ^A | AWG | Class B | | Class C | | Class D | | | Reverse Concentric Compressed Class B Diameter, in. | Unilay Compressed Class B Diameter, in. | Ω/1000 ft | Ω/km |
| | | | | Number of Wires | Diameter of Wire, mils ^B | Number of Wires | Diameter of Wire, mils ^A | Number of Wires | Diameter of Wire, mils ^A | | | | | |
| 4 000 000 | ... | 2 520 000 | ... | 217 | 135.8 | 271 | 121.5 | 271 | 121.5 | ... | ... | 0.00442 | 0.0145 | |
| 3 500 000 | ... | 2 200 000 | ... | 169 | 143.9 | 217 | 127.0 | 271 | 113.6 | ... | ... | 0.00505 | 0.0166 | |
| 3 000 000 | ... | 1 890 000 | ... | 169 | 133.2 | 217 | 117.6 | 271 | 105.2 | ... | ... | 0.00584 | 0.0192 | |
| 2 500 000 | ... | 1 570 000 | ... | 127 | 140.3 | 169 | 121.6 | 217 | 107.3 | ... | ... | 0.00701 | 0.0229 | |
| 2 000 000 | ... | 1 260 000 | ... | 127 | 125.5 | 169 | 108.8 | 217 | 96.0 | 1.583 | 1.533 | 0.00867 | 0.0284 | |
| 1 900 000 | ... | 1 195 000 | ... | 127 | 122.3 | 169 | 106.0 | 217 | 93.6 | 1.542 | 1.494 | 0.00913 | 0.0299 | |
| 1 800 000 | ... | 1 132 000 | ... | 127 | 119.1 | 169 | 103.2 | 217 | 91.1 | 1.502 | 1.454 | 0.00963 | 0.0316 | |
| 1 750 000 | ... | 1 101 000 | ... | 127 | 117.4 | 169 | 101.8 | 217 | 89.8 | 1.480 | 1.434 | 0.0099 | 0.0325 | |
| 1 700 000 | ... | 1 069 000 | ... | 127 | 115.7 | 169 | 100.3 | 217 | 88.5 | 1.459 | 1.413 | 0.0102 | 0.0335 | |
| 1 600 000 ^C | ... | 1 006 000 | ... | 127 | 112.2 | 169 | 97.3 | 217 | 85.9 | 1.415 | 1.371 | 0.0109 | 0.0357 | |
| 1 500 000 | ... | 943 000 | ... | 91 | 128.4 | 127 | 108.7 | 169 | 94.2 | 1.370 | 1.327 | 0.0116 | 0.0380 | |
| 1 400 000 | ... | 880 000 | ... | 91 | 124.0 | 127 | 105.0 | 169 | 91.0 | 1.323 | 1.282 | 0.0124 | 0.0407 | |
| 1 300 000 | ... | 818 000 | ... | 91 | 119.5 | 127 | 101.2 | 169 | 87.7 | 1.275 | 1.236 | 0.0133 | 0.0436 | |
| 1 250 000 ^C | ... | 786 000 | ... | 91 | 117.2 | 127 | 99.2 | 169 | 86.0 | 1.250 | 1.212 | 0.0138 | 0.0453 | |
| 1 200 000 | ... | 755 000 | ... | 91 | 114.8 | 127 | 97.2 | 169 | 84.3 | 1.225 | 1.187 | 0.0144 | 0.0472 | |
| 1 100 000 | ... | 692 000 | ... | 91 | 109.9 | 127 | 93.1 | 169 | 80.7 | 1.173 | 1.137 | 0.0158 | 0.0518 | |
| 1 000 000 ^B | ... | 629 000 | ... | 61 | 128.0 | 91 | 104.8 | 127 | 88.7 | 1.117 | 1.084 | 0.0173 | 0.0568 | |
| 900 000 | ... | 566 000 | ... | 61 | 121.5 | 91 | 99.4 | 127 | 84.2 | 1.060 | 1.028 | 0.0193 | 0.0633 | |
| 800 000 ^C | ... | 503 000 | ... | 61 | 114.5 | 91 | 93.8 | 127 | 79.4 | 1.000 | 0.969 | 0.0217 | 0.0712 | |
| 750 000 | ... | 472 000 | ... | 61 | 110.9 | 91 | 90.8 | 127 | 76.8 | 0.968 | 0.939 | 0.0231 | 0.0758 | |
| 700 000 | ... | 440 000 | ... | 61 | 107.1 | 91 | 87.7 | 127 | 74.2 | 0.935 | 0.907 | 0.0248 | 0.0814 | |
| 650 000 | ... | 409 000 | ... | 61 | 103.2 | 91 | 84.5 | 127 | 71.5 | 0.901 | 0.874 | 0.0267 | 0.0876 | |
| 636 000 | ... | 400 000 | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | |
| 600 000 | ... | 377 000 | ... | 61 | 99.2 | 91 | 81.2 | 127 | 68.7 | 0.866 | 0.840 | 0.0289 | 0.0948 | |
| 550 000 | ... | 346 000 | ... | 61 | 95.0 | 91 | 77.7 | 127 | 65.8 | 0.829 | 0.804 | 0.0315 | 0.103 | |
| 500 000 | ... | 314 000 | ... | 37 | 116.2 | 61 | 90.5 | 91 | 74.1 | 0.789 | 0.766 | 0.0347 | 0.114 | |
| 477 000 | ... | 300 000 | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | |
| 450 000 | ... | 283 000 | ... | 37 | 110.3 | 61 | 85.9 | 91 | 70.3 | 0.749 | 0.727 | 0.0385 | 0.126 | |
| 400 000 ^C | ... | 252 000 | ... | 37 | 104.0 | 61 | 81.0 | 91 | 66.3 | 0.706 | 0.685 | 0.0434 | 0.142 | |
| 350 000 | ... | 220 000 | ... | 37 | 97.3 | 61 | 75.7 | 91 | 62.0 | 0.661 | 0.641 | 0.0495 | 0.162 | |
| 336 400 | ... | ... | 0000 | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | |
| 300 000 | ... | 188 700 | ... | 37 | 90.0 | 61 | 70.1 | 91 | 57.4 | 0.611 | 0.594 | 0.0578 | 0.187 | |
| 266 800 | ... | ... | 000 | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | |
| 250 000 | ... | 157 200 | ... | 37 | 82.2 | 61 | 64.0 | 91 | 52.4 | 0.558 | 0.542 | 0.0694 | 0.228 | |
| 211 600 | 0000 | ... | 00 | 19 | 105.5 | 37 | 75.6 | 61 | 58.9 | 0.512 | 0.498 | 0.0820 | 0.269 | |
| 167 800 | 000 | ... | 0 | 19 | 94.0 | 37 | 67.3 | 61 | 52.4 | 0.456 | 0.443 | 0.103 | 0.338 | |
| 133 100 | 00 | ... | 1 | 19 | 83.7 | 37 | 60.0 | 61 | 46.7 | 0.405 | 0.395 | 0.130 | 0.427 | |
| 105 600 | 0 | ... | 2 | 19 | 74.5 | 37 | 53.4 | 61 | 41.6 | 0.362 | 0.352 | 0.164 | 0.538 | |
| 83 690 | 1 | ... | 3 | 19 | 66.4 | 37 | 47.6 | 61 | 37.0 | 0.322 | 0.313 | 0.207 | 0.679 | |
| 66 360 | 2 | ... | 4 | 7 | 97.4 | 19 | 59.1 | 37 | 42.4 | 0.283 | ... | 0.261 | 0.856 | |
| 52 620 | 3 | ... | 5 | 7 | 86.7 | 19 | 52.6 | 37 | 37.7 | 0.252 | ... | 0.330 | 1.08 | |
| 41 740 | 4 | ... | 6 | 7 | 77.2 | 19 | 46.9 | 37 | 33.6 | 0.225 | ... | 0.416 | 1.36 | |
| 33 090 | 5 | ... | 7 | 7 | 68.8 | 19 | 41.7 | 37 | 29.9 | 0.200 | ... | 0.523 | 1.72 | |
| 26 240 | 6 | ... | 8 | 7 | 61.2 | 19 | 37.2 | 37 | 26.6 | 0.178 | ... | 0.661 | 2.17 | |
| 20 820 | 7 | ... | 9 | 7 | 54.5 | 19 | 33.1 | 37 | 23.7 | 0.159 | ... | 0.834 | 2.74 | |
| 16 510 | 8 | ... | 10 | 7 | 48.6 | 19 | 29.5 | 37 | 21.1 | 0.142 | ... | 1.05 | 3.44 | |
| 13 090 | 9 | ... | 11 | 7 | 43.2 | 19 | 26.2 | 37 | 18.8 | 0.126 | ... | 1.32 | 4.33 | |
| 10 380 | 10 | ... | 12 | 7 | 38.5 | 19 | 23.4 | 37 | 16.7 | 0.113 | ... | 1.67 | 5.48 | |
| | 11 | ... | ... | ... | ... | ... | ... | ... | ... | 0.100 | ... | 2.11 | 6.92 | |
| 6530 | 12 | ... | 14 | 7 | 30.5 | 19 | 18.5 | 37 | 13.3 | 0.089 | ... | 2.67 | 8.76 | |
| | 13 | ... | ... | ... | ... | ... | ... | ... | ... | 0.080 | ... | 3.34 | 10.96 | |
| 4110 | 14 | ... | 16 | 7 | 24.2 | 19 | 14.7 | 37 | 10.5 | 0.071 | ... | 4.22 | 13.8 | |
| 2580 | 16 | ... | 18 | 7 | 19.2 | 19 | 11.7 | ... | ... | ... | ... | 6.71 | 22.0 | |
| 1620 | 18 | ... | 20 | 7 | 15.2 | ... | ... | ... | ... | ... | ... | 10.7 | 35.1 | |
| 1020 | 20 | ... | 22 | 7 | 12.1 | ... | ... | ... | ... | ... | ... | 16.9 | 55.4 | |

^A See Footnote B of Table 1.

^B This size is sensibly equivalent to size 1 033 500 cmils within a difference of 3.24 %.

^C These sizes are sensibly equivalent to sizes 1 590 000; 1 272 000; 795 000; and 397 500 cmil respectively within the cross-sectional area tolerances stipulated by this specification and associated Specifications B 230/B 230M and B 609/B 609M.

TABLE 4 Construction Requirements of Conductors Classes B, C, and D

NOTE 1—Sizes selected from Specification B 682.

| Conductor Size, mm ² | Stranding | | | | | | Nominal Diameter (mm) | | |
|------------------------------------|---------------------------------|--------------|---------------------------------|--------------|---------------------------------|--------------|--|-----------------------------------|--------------------------------------|
| | Class B | | Class C | | Class D | | Reverse Con- centric Com- pressed Class B | Unilay Com- pressed Class B | Direct Current Resistance Ω/km |
| | Number of Wires ^A | Diameter, mm | Number of Wires ^A | Diameter, mm | Number of Wires ^A | Diameter, mm | | | |
| 2000 | 217 | 3.43 | 271 | 3.07 | 271 | 3.07 | 56.56 | 54.74 | 0.01437 |
| 1800 | 169 | 3.68 | 217 | 3.25 | 271 | 2.91 | 53.54 | 51.93 | 0.01596 |
| 1600 | 169 | 3.47 | 217 | 3.06 | 271 | 2.74 | 50.49 | 48.96 | 0.01796 |
| 1400 | 169 | 3.25 | 217 | 2.87 | 271 | 2.56 | 47.29 | 45.79 | 0.02053 |
| 1250 | 127 | 3.54 | 169 | 3.07 | 217 | 2.71 | 44.64 | 43.27 | 0.02299 |
| 1200 ^B | 127 | 3.47 | 169 | 3.01 | 217 | 2.65 | 43.76 | 42.40 | 0.02395 |
| 1120 | 127 | 3.35 | 169 | 2.90 | 217 | 2.56 | 42.24 | 40.96 | 0.02566 |
| 1000 | 127 | 3.17 | 169 | 2.74 | 217 | 2.42 | 39.97 | 38.70 | 0.02874 |
| 900 | 127 | 3.00 | 169 | 2.60 | 217 | 2.30 | 37.83 | 36.72 | 0.03193 |
| 800 | 91 | 3.35 | 127 | 2.83 | 169 | 2.46 | 35.74 | 34.62 | 0.03592 |
| 710 | 91 | 3.15 | 127 | 2.67 | 169 | 2.31 | 33.61 | 32.61 | 0.04047 |
| 630 | 91 | 2.97 | 127 | 2.51 | 169 | 2.18 | 31.69 | 29.98 | 0.04561 |
| 560 | 91 | 2.80 | 127 | 2.37 | 169 | 2.05 | 29.88 | 28.96 | 0.05131 |
| 500 | 61 | 3.23 | 91 | 2.64 | 127 | 2.24 | 28.20 | 27.37 | 0.05747 |
| 450 | 61 | 3.06 | 91 | 2.51 | 127 | 2.12 | 26.71 | 25.96 | 0.06386 |
| 400 | 61 | 2.89 | 91 | 2.37 | 127 | 2.00 | 25.23 | 24.48 | 0.07184 |
| 355 | 61 | 2.72 | 91 | 2.23 | 127 | 1.89 | 23.75 | 23.06 | 0.08094 |
| 315 | 61 | 2.56 | 91 | 2.10 | 127 | 1.78 | 22.35 | 21.72 | 0.09122 |
| 300 ^B | 61 | 2.50 | 91 | 2.05 | 127 | 1.73 | 21.83 | 21.20 | 0.09578 |
| 280 | 61 | 2.42 | 91 | 1.98 | 127 | 1.68 | 21.13 | 20.48 | 0.10263 |
| 250 | 37 | 2.93 | 61 | 2.28 | 91 | 1.87 | 19.89 | 19.35 | 0.11494 |
| 240 ^B | 37 | 2.87 | 61 | 2.24 | 91 | 1.83 | 19.49 | 18.96 | 0.11973 |
| 224 | 37 | 2.78 | 61 | 2.16 | 91 | 1.77 | 18.88 | 18.32 | 0.12828 |
| 200 | 37 | 2.62 | 61 | 2.04 | 91 | 1.67 | 17.79 | 17.31 | 0.14368 |
| 185 ^B | 37 | 2.52 | 61 | 1.97 | 91 | 1.61 | 17.11 | 16.65 | 0.15532 |
| 180 | 37 | 2.49 | 61 | 1.94 | 91 | 1.59 | 16.90 | 16.42 | 0.15964 |
| 160 | 37 | 2.35 | 61 | 1.83 | 91 | 1.50 | 15.96 | 15.48 | 0.17959 |
| 150 ^B | 37 | 2.27 | 61 | 1.77 | 91 | 1.45 | 15.41 | 14.99 | 0.19157 |
| 140 | 37 | 2.19 | 61 | 1.71 | 91 | 1.40 | 14.87 | 14.48 | 0.20525 |
| 125 | 37 | 2.07 | 61 | 1.62 | 91 | 1.32 | 14.06 | 13.68 | 0.22988 |
| 120 ^B | 37 | 2.03 | 61 | 1.58 | 91 | 1.30 | 13.78 | 13.41 | 0.23946 |
| 100 | 19 | 2.59 | 37 | 1.86 | 61 | 1.44 | 12.56 | 12.24 | 0.28735 |
| 95.0 ^B | 19 | 2.52 | 37 | 1.81 | 61 | 1.41 | 12.22 | 11.93 | 0.30247 |
| 80.0 | 19 | 2.32 | 37 | 1.66 | 61 | 1.29 | 11.25 | 10.95 | 0.35919 |
| 70.0 ^B | 19 | 2.17 | 37 | 1.55 | 61 | 1.21 | 10.52 | 10.24 | 0.4105 |
| 63.0 | 19 | 2.05 | 37 | 1.47 | 61 | 1.15 | 9.94 | 9.71 | 0.45611 |
| 50.0 | 19 | 1.83 | 37 | 1.31 | 61 | 1.02 | 8.88 | 8.65 | 0.5747 |
| 40.0 | 19 | 1.64 | 37 | 1.17 | 61 | 0.914 | 7.95 | 7.74 | 0.71838 |
| 35.0 ^B | 7 | 2.52 | 19 | 1.53 | 37 | 1.10 | 7.33 | ... | 0.821 |
| 31.5 | 7 | 2.39 | 19 | 1.45 | 37 | 1.04 | 6.95 | ... | 0.91222 |
| 25.0 | 7 | 2.13 | 19 | 1.29 | 37 | 0.928 | 6.20 | ... | 1.1494 |
| 20.0 | 7 | 1.91 | 19 | 1.16 | 37 | 0.830 | 5.56 | ... | 1.4368 |
| 16.0 | 7 | 1.71 | 19 | 1.04 | 37 | 0.742 | 4.98 | ... | 1.7959 |
| 12.5 | 7 | 1.51 | 19 | 0.915 | 37 | 0.656 | 4.39 | ... | 2.2988 |
| 10.0 | 7 | 1.35 | 19 | 0.819 | 37 | 0.587 | 3.93 | ... | 2.8735 |
| 8.00 | 7 | 1.21 | 19 | 0.732 | 37 | 0.525 | 3.52 | ... | 3.5919 |
| 6.30 | 7 | 1.07 | 19 | 0.650 | 37 | 0.466 | 3.11 | ... | 4.5611 |
| 6.00 ^B | 7 | 1.04 | 19 | 0.634 | 37 | 0.454 | 3.03 | ... | 4.7892 |
| 5.00 | 7 | 0.954 | 19 | 0.579 | 37 | 0.415 | 2.78 | ... | 5.747 |
| 4.00 | 7 | 0.853 | 19 | 0.518 | 37 | 0.371 | 2.48 | ... | 7.1838 |
| 3.15 | 7 | 0.757 | 19 | 0.459 | 37 | 0.329 | 2.20 | ... | 9.1222 |
| 2.50 | 7 | 0.674 | 19 | 0.409 | 37 | 0.293 | 1.96 | ... | 11.494 |
| 2.00 | 7 | 0.603 | 19 | 0.366 | 37 | 0.262 | 1.75 | ... | 14.368 |
| 1.50 ^B | 7 | 0.522 | 19 | 0.317 | 37 | 0.227 | 1.52 | ... | 19.157 |
| 1.00 | 7 | 0.426 | 19 | 0.259 | ... | ... | 1.24 | ... | 28.735 |
| 0.800 | 7 | 0.381 | ... | ... | ... | ... | 1.11 | ... | 35.919 |
| 0.750 ^B | 7 | 0.369 | ... | ... | ... | ... | 1.07 | ... | 38.313 |
| 0.500 | 7 | 0.302 | ... | ... | ... | ... | 0.88 | ... | 57.47 |

^A For unidirectional/unilay stranded conductors, the number of wires shown are a minimum.

^B Additional sizes shown as third preference sizes in Specification B 682.

TABLE 5 Minimum Distance Between Joints in the Completed Conductor

| Number of Wires in Conductor ^A | Distance Between Joints, min ft [m] | | | | | |
|---|-------------------------------------|-------------------|-----------------|-------------------|---------------------|--------------------|
| | Class AA | | Class A | | Classes B, C, and D | |
| | ft | [m] | ft | [m] | ft | [m] |
| 7 | 50 ^B | [15] ^B | 50 ^C | [15] ^C | 1 | [0.3] |
| 12 | 50 | [15] | 50 | [15] | 1 | [0.3] |
| 19 | 50 | [15] | 50 | [15] | 1 | [0.3] |
| 37 | 25 | [7.5] | 25 | [7.5] | 1 ^D | [0.3] ^D |
| 61 and over | 25 | [7.5] | 5 | [1.5] | 1 ^D | [0.3] ^D |

^A Conductors of an intermediate number of wires shall conform to those having the next smaller number.

^B Only cold-pressure welds and electric-butt, cold-upset welds are permitted in the six outer wires of conductors composed of seven wires; no welds are permitted in the center or core wire.

^C For bare overhead conductors only cold-pressure welds and electric-butt, cold-upset welds are permitted in the six outer wires, no welds are permitted in the center or core wire. For other uses, electric-butt welds, cold-pressure welds, and electric-butt, cold-upset welds may be used in any wire.

^D In a layer.

7.5 The direction of lay for conductors having a nominal cross-sectional area larger than No. 8 AWG (8 mm²) shall be reversed in successive layers, unless otherwise specified by the purchaser.

7.5.1 For conductors to be used in covered or insulated wires or cables, the direction of lay of the outer layer shall be left hand and may be reversed or unidirectional/unilay in successive layers, unless otherwise agreed upon with the purchaser.

8. Construction

8.1 The areas of cross section, numbers, and diameters of wires in the various classes of concentric-lay-stranded conductors shall conform to the requirements prescribed in Tables 1-4.

8.2 The diameters of the wires listed in Tables 3 and 4 are nominal. Where “combination strand” is required in order to insulate the conductor properly, wires of different diameters may be used provided that the area of cross section after stranding is in accordance with Section 12.

8.3 Where compressed stranding is required in order to insulate the conductor properly, one or more layers of any stranded conductor consisting of 7 wires or more may be slightly compressed, thereby reducing the outside diameter of the conductor to the nominal values shown in Table 3 or Table 4, provided that the area of cross section after compressing is in accordance with Section 12.

8.3.1 The average diameter of the conductor in 8.3 shall vary by not more than +1 or -2 % from the diameter specified in Table 3 or Table 4.

8.4 The nominal overall diameter of a Class A and AA stranded conductor shall be calculated based on the numerical sum of the diameter thickness of the individual strand wire component in the conductor. The diameter of the individual strand wire component shall be as specified in Table 1 and Table 2 and this diameter shall be referred to as the “mean diameter” value. The minimum and maximum overall diameter of a Class A and AA stranded conductor shall be based on calculations made using the mean diameter tolerances as specified by Specification B 230/B 230M for the corresponding strand wire size.

9. Rated Strength of Conductor

9.1 The rated strength of 1350-H19 conductors shall be taken as the percent, indicated in Table 6, of the sum of the strengths of the component wires, calculated using the nominal wire diameters and the specified minimum average tensile strength given in Specification B 230/B 230M for 1350-H19 wire. In the case of compressed conductors, the nominal wire diameter should be that of the corresponding non-compressed construction as listed in Tables 1-4.

9.2 Calculations for rated strengths of 1350-H16, -H26, -H14, -H24, -H142, and -H242 conductors shall be made on the basis of the strengths of the component wires using the nominal wire diameters and the specified maximum and minimum tensile strengths for the appropriate temper of the respective component wires given in Specification B 609/B 609M. The minimum rated strengths of the conductors shall be taken as the sum of the calculated minimum strengths of the component wires multiplied by the rating factor given in Table 6. The maximum rated strength of the conductors shall be taken as the sum of the calculated maximum strengths of the component wires.

9.3 Rated-strength and breaking-strength values shall be rounded to three significant figures, in the final value only, in accordance with the rounding method of Practice E 29.

9.4 Rated strengths of conductors are given in Table 1 or Table 2.

10. Density

10.1 For the purpose of calculating mass, cross sections, and so forth, the density of aluminum 1350 shall be taken as 2705 kg/m³[0.0975 lb/in.³] at 20°C.

11. Mass and Electrical Resistance

11.1 The mass and electrical resistance of a unit length of a stranded conductor are a function of the length of lay. The approximate mass and electrical resistance may be determined using the standard increments shown in Table 7. When greater accuracy is desired, the increment based on the specific lay of the conductor may be calculated (Explanatory Note 5).

11.2 The maximum electrical resistance of a unit length of stranded conductor shall not exceed 2 % over the nominal dc resistance shown in Tables 3 and 4 (Explanatory Note 8). When the dc resistance is measured at other than 20°C, it is to be corrected by using the multiplying factor given in Table 8.

11.3 For conductors to be used in covered or insulated wires or cables dc resistance measurement may be used in lieu of the method outlined in Section 12, to determine compliance with this specification.

TABLE 6 Rating Factors

| Stranding | | Rating Factor, % |
|------------------------------|------------------|------------------|
| Number of Wires in Conductor | Number of Layers | |
| 7 | 1 | 96 |
| 19 | 2 | 93 |
| 37 | 3 | 91 |
| 61 | 4 | 90 |
| 91 and above | 5 and above | 89 |



TABLE 7 Standard Increments Due to Stranding

| Size of Conductor, All Classes, cmils [mm ²] | Increment (Increase) of Mass and Electrical Resistance, % |
|--|---|
| 4 000 000 to 3 000 001, incl [2000–1500, incl] | 4 |
| 3 000 000 to 2 000 001, incl [Under 1500–1000, incl] | 3 |
| 2 000 000 and under [Under 1000] | 2 |

TABLE 8 Temperature Correction Factors for Conductor Resistance

| Temperature, °C | Multiplying Factor for Conversion to 20°C |
|-----------------|---|
| 0 | 1.088 |
| 5 | 1.064 |
| 10 | 1.042 |
| 15 | 1.020 |
| 20 | 1.000 |
| 25 | 0.980 |
| 30 | 0.961 |
| 35 | 0.943 |
| 40 | 0.925 |
| 45 | 0.908 |
| 50 | 0.892 |
| 55 | 0.876 |
| 60 | 0.861 |
| 65 | 0.846 |
| 70 | 0.832 |
| 75 | 0.818 |
| 80 | 0.805 |
| 85 | 0.792 |
| 90 | 0.780 |

12. Variation in Area

12.1 The area of cross section of the completed conductor shall not be less than 98 % of the area of cross section of the conductor size listed in Column 1 of Tables 1-4. The manufacturer may have the option of determining the cross-sectional area by either of the following methods, except that in case of question regarding area compliance, the method of 12.1.2 shall be used.

12.1.1 The area of cross section of a conductor may be determined by calculations from diameter measurements, ex-

pressed to four decimal places, of its component wires at any point when measured perpendicularly to their axes.

12.1.2 The area of cross section of a conductor may be determined by Test Method B 263. In applying that test method, the increment in mass resulting from stranding may be the applicable value specified in 11.1 or may be calculated from the measured component dimensions of the sample under test. In case of question regarding area compliance, the actual mass increment due to stranding shall be calculated.

13. Finish

13.1 The conductor shall be free of all imperfections not consistent with good commercial practice.

14. Mechanical and Electrical Tests of Conductors NOT Annealed After Stranding

14.1 Wires composing the conductors shall be tested prior to stranding in accordance with the applicable specification (see 5.2), and tests on the completed conductor are not required. However, when requested by the purchaser and agreed to by the manufacturer at time of ordering, the tension tests of wires before stranding may be waived and the completed conductor tested in accordance with 14.2, or wires removed from the completed conductor tested in accordance with 14.3.

14.2 When the completed conductor is tested as a unit, the breaking strength shall be not less than the rated strength of 1350-H19 conductors or the minimum rated strength of 1350-H16, -H26, -H14, -H24, -H142, and -H242 conductors if failure occurs in the free length at least 1 in. [25 mm] beyond the end of either gripping device, or shall be not less than 95 % of the rated or minimum rated strength if failure occurs inside, or within 1 in. [25 mm] of the end of either gripping device. The breaking strength of 1350-H16, -H26, -H14, -H24, -H142, and -H242 conductors shall be not greater than their maximum rated strengths. The free length between grips of the test specimen shall be not less than 24 in. [600 mm] and care shall be taken to ensure that the wires in the conductor are evenly gripped during the test (Explanatory Note 6).

14.3 Routine production testing of the aluminum wires after stranding is not required. However, when such tests are

TABLE 9 Dimensions of Standard Reels (For Information Only)

| Reel Designation ^{A,B,C} | Reel Capacity, in. ³ [m ³] | Nominal Reel Dimensions | | | | |
|-----------------------------------|--|--------------------------------|------------------------------|----------------|---------------|-------------------------------------|
| | | Flange Diameter, in. [m] | Drum Diameter, in. [m] | Width, in. [m] | | Arbor Hole Diameter, in. [mm] |
| | | | | Inside | Outside | |
| NR 36.22 | 16 800 [0.275] | 36 [0.91] | 18 [0.46] | 22 [0.56] | 25 [0.64] | 3 to 3/4 [76–83] |
| NR 42.28 | 29 100 [0.477] | 42 [1.07] | 21 [0.53] | 28 [0.71] | 32 1/2 [0.83] | 3 to 3/4 [76–83] |
| NR 48.28 | 38 000 [0.623] | 48 [1.22] | 24 [0.61] | 28 [0.71] | 32 1/2 [0.83] | 3 to 3/4 [76–83] |
| RM 66.32 ^D | 76 900 [1.260] | 66 [1.68] | 36 [0.91] | 32 [0.81] | 38 [0.97] | 3 to 3/4 [76–83] |
| RM 68.38 ^D | 99 300 [1.627] | 68 [1.73] | 36 [0.91] | 38 [0.97] | 44 [1.12] | 3 to 3/4 [76–83] |
| RMT 84.45 ^E | 152 700 [2.502] | 78 (84) [1.98 (2.13)] | 42 [1.07] | 45 [1.14] | 52 [1.32] | 5 to 5/4 [127–133] |
| RMT 90.45 ^E | 187 000 [3.064] | 84 (90) [2.13 (2.29)] | 42 [1.07] | 45 [1.14] | 52 [1.32] | 5 to 5/4 [127–133] |

^A Prefix “NR” denotes wooden nonreturnable reel, “RM” metal returnable reel, and “RMT” metal returnable reel with I-beam tires.
^B Pay-off equipment for reels NR 48.28 and smaller should be a minimum of 2 in. [50 mm] wider than the nominal outside reel width to provide for extension of bolts and for possible flange distortion. For reels 66.32 and larger, either wood or metal, pay-off equipment should not be less than 4 in. [100 mm] wider than the reel width.
^C Reels are not designed to withstand the forces required for braking during tension stringing operations.
^D Reels RM 66.32 and RM 68.38 have flat rims.
^E Reels RMT 84.45 and RMT 90.45 have 3-in. [76-mm] I-beam tires. Indicated flange diameters are diameters under the tire; values in parentheses are diameters over the tire. Reels with similar dimensions except without I-beam tires are sometimes used.

requested by the purchaser and agreed upon by the manufacturer at the time of ordering (or made for other reasons), the 1350-H19 wires removed from the completed conductor shall have tensile strengths of not less than 95 % of the minimum tensile strength specified for the individual tests in Specification B 230/B 230M. The 1350-H16, -H26, -H14, -H24, -H142, and -H242 wires shall have tensile strengths not less than 95 % of the minimum tensile strengths nor more than 105 % of the maximum tensile strengths prescribed in Specification B 609/B 609M. The electrical resistivity shall meet the minimum resistivity specified for the wire before stranding. Elongation tests may be made for information purposes only and no minimum values are assigned (Explanatory Note 7). The frequency of these tests shall be decided upon between the purchaser and the manufacturer.

14.4 All wires composing the conductors shall be capable of meeting the bending properties stated in Specification B 230/B 230M after stranding.

15. Mechanical and Electrical Tests of Conductors ANNEALED After Stranding

15.1 Tensile properties and electrical resistivity shall be determined on samples taken from 10 % of the reels or coils of conductor, but from not less than five (or all if the lot is less than five) reels or coils. Resistivity shall be determined as prescribed in Section 7 of Specification B 230/B 230M on one wire from each conductor sample except this test is not required if performed previously on the 1350-H19 wire. At the manufacturer's option, tension tests shall be made either on one of the inner 7 wires and one wire from each additional layer of each conductor sample to determine conformance with 15.2 or on the conductor as a unit to determine conformance with 15.3.

15.2 When wires removed from the completed conductor are tested, 1350-H26, -H24, and -H242 wires shall have tensile strengths not less than 95 % of the minimum tensile strength nor more than 105 % of the maximum tensile strength prescribed in Specification B 609/B 609M, as applicable (Explanatory Note 7).

15.3 When the completed conductor is tested as a unit, the breaking strengths of 1350-H26, -H24, and -H242 conductors shall conform with 9.2 through 9.4.

15.4 All wires composing the conductors shall be capable of meeting the bending properties stated in Specification B 230/B 230M after stranding. Routine production testing after stranding is not required unless requested by the purchaser and agreed upon by the manufacturer at the time of ordering.

16. Retests

16.1 If upon testing a sample from any reel or coil of conductor the results do not conform to the requirements of Sections 8 and 9, two additional samples shall be tested, and the average of the three tests shall determine the acceptance of the reel or coil.

17. Inspection

17.1 Unless otherwise specified in the contract or purchase order, the manufacturer shall be responsible for the performance of all inspection and test requirements specified.

17.2 All inspections and tests shall be made at the place of manufacture unless otherwise especially agreed to between the manufacturer and the purchaser at the time of the purchase.

17.3 The manufacturer shall afford the inspector representing the purchaser all reasonable access to the manufacturer's facilities to satisfy him that the material is being furnished in accordance with this specification.

18. Packaging and Package Marking

18.1 Package sizes and kind of package, reels or coils, shall be agreed upon by the manufacturer and the purchaser at the time of placing the order. Recommended package sizes for Classes AA and A are shown in Table 1 or Table 2.

18.2 There shall be only one length of conductor on a reel when the conductor on the reel will not undergo further manufacturing processes.

18.3 The conductor shall be protected against damage in ordinary handling and shipping. If heavy wood lagging is required, it shall be specified by the purchaser at the time of placing the order.

18.4 The net mass, length (and number of lengths if more than one is included in a package), size, kind of conductor, stranding, and any other necessary identification shall be marked on a tag attached to the end of the conductor inside the package. This same information, together with the purchase order number, the manufacturer's serial number (if any), and all shipping marks and other information required by the purchaser shall appear on the outside of each package.

NOTE 4—Multiple lengths per package are allowable only when the bare conductor is intended for remanufacture, such as adding a covering or insulation. In such cases the position of each end of a length is to be clearly marked and the length of each portion shall be shown on the tag attached to the end of the conductor.

19. Marking

19.1 The net mass, length (and number of lengths, if more than one length is included in a package), size, and kind of conductor shall be marked on a tag attached to the end of each conductor inside the package. The same information, together with the manufacturer's serial number (if any) and all shipping marks and other information required by the purchaser, all appear on the outside of each package.

20. Keywords

20.1 aluminum conductor; concentric-lay-stranded aluminum conductor; electrical conductors; electrical conductors, aluminum; stranded aluminum conductors

EXPLANATORY NOTES

NOTE 1—In this specification only concentric-lay-stranded conductor constructions manufactured from round aluminum 1350 wires are specifically designated.

NOTE 2—For definitions of terms relating to conductors, refer to Terminology B 354.

NOTE 3—The behavior of properly spaced wire joints in stranded conductors is related to both their tensile strength and elongation. Because of its higher elongation properties, the lower strength electric-butt weld gives equivalent overall performance to that of a cold-pressure weld or an electric-butt, cold-upset weld in stranded conductors with more than seven wires.

NOTE 4—Certain types of insulated conductors may require a shorter lay than other conductors. Special requirements regarding length of lay should be specified by the purchaser in such instances.

NOTE 5—The increment of mass or electrical resistance of a completed concentric-lay-stranded conductor, k , in percent is:

$$k = 100(m - 1)$$

where m is the stranding factor, and is also the ratio of the mass or electrical resistance of a unit length of stranded conductor to that of a solid conductor of the same cross-sectional area or of a stranded conductor with infinite length of stranding, that is, all wires parallel to the conductor axis. The stranding factor m for the completed stranded conductor is the numerical average of the stranding factors for each of the individual wires in the conductor, including the straight core wire, if any (for which the stranding factor is unity). The stranding factor (mind) for any given wire in a concentric-lay-stranded conductor is:

$$m_{ind} = \sqrt{1 + (9.8696/n^2)}$$

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).

where n = length of lay/diameter of helical path of the wire. The derivation of the above is given in *NBS Handbook 100*.

NOTE 6—To test stranded conductors for breaking strength successfully as a unit requires an adequate means of gripping the ends of the test specimen without causing damage that may result in failure below the actual strength of the conductor. Various means are available such as compression sleeves, split sleeves, and preformed grips, but ordinary jaws or clamping devices usually are not suitable.

NOTE 7—Wires unlaidd from conductors may have different physical properties from those of the wire prior to stranding because of the deformation brought about by stranding and straightening for test.

NOTE 8—The dc resistance on a given construction shall be calculated using the following formula:

Inch-Pound Units:

$$R = \left(\frac{k}{100} + 1 \right) \frac{\rho}{A}$$

or Metric Units:

$$R \left[\left(\frac{K}{100} + 1 \right) \frac{\rho}{A} \right] 1000$$

where:

- R = conductor resistance in $\Omega/1000$ ft (Ω/km),
- k = increment due to stranding from Table 7 and Explanatory Note 5,
- ρ = volume resistivity in ohms-cmil/ft ($\Omega\text{-mm}^2/\text{m}$), determined in accordance with Test Method B 193, and
- A = cross-sectional area of conductor in kcmil (mm^2) determined in accordance with Section 12 of this specification.